



L-512 Tablet Dissolved Oxygen Meter

Main Features

- 5 inch LCD screen with wide 150° viewing angle, beautiful and compact design.
- Compact bench cradle with rotary electrode holder to save space in laboratory.
- Small size and portable make it easy to carry and remove in laboratory and outdoors.
- Extendibility: different electrodes can be installed to test pH, conductivity and dissolved oxygen.
- Auto recognition of different electrodes after electrode is connected.
- 3.5 mm jack input for electrodes makes it very easy for electrode connection.
- Two USB and one SD card interfaces for power and data transfer.
- Can store 300 pieces of data including readings, date and time.
- Rechargeable and long lasting battery. Auto shut off if there is no operation in ten minutes.

Specifications

Display	5-inch LCD screen
Parameters	Concentration, saturation, temperature
DO Range	0.00~20 mg/L (ppm)
Resolution	0.01/0.1
DO Accuracy	±0.3%, ±0.4mg/L
DO Saturation	0.0~200%
Saturation Resolution	0.1%
Saturation Accuracy	±2.0%FS
Temperature Measuring Range	(0~100) °C
Temperature Resolution	0.1 °C
Temperature Accuracy	5~60 °C: ±0.5 °C, Others: ±1.0 °C
Temperature compensation range	(0~100) °C (automatic)
Salinity compensation range	(0.0~50.0)g/L
Air pressure compensation range	(80~105)kPa(automatic)
Pressure resolution	1
Pressure Accuracy	±2%
Stability	(±0.07mg/L)/1h
Response time	≤30s(25 °C, 90% response)
Data Storage	300 data, external USB storage
Communication Interfaces	USB
Working Conditions	Temperature: 5~40° Humidity: 5~85%
Power Requirements	DC 5V/1A
Size & Weight	190×130×10mm/300g